

APPLICATIONS:

The **DH-SK** incorporates a unique flat platform that combines the **benefits of a column lift** coupled to the huge **benefits of a slider lift**, such as the increased platform depth, easier accessibility to loading docks by clearance of the vehicle's rear frame, the hydraulic adjustable tilt of the platform, and the stability of a 4 cylinder tail lift,...

The platform is available in a wide variety of configurations, such as:

- folding platform (increased depth) or **1 firm steel section only**
- fixed leading edge or **hinged leading edge** in 2 or 4 sections
- standard flush platform side or **side loading ramps**
- the hinged leading edge and side loading ramps can be raised in the vertical position to serve as **pallet stop**.



DH-SK in road position



DH-SK with firm steel platform of 1300mm, hinged leading edge & side loading ramps



DH-SK with 1500 mm folding steel / alu platform & front loading ramps

GENERAL SPECIFICATIONS:

- **Flat steel/aluminium platform with fixed leading edge or hinged leading edge in 2 independant sections** as an option (auto-adjusting at the ground level, option [S701])
- Hinged leading edge can be put in vertical position as pallet stop
- 2 single acting lift and 2 tilt cylinders
- Hydraulic tilting of the platform adjustable in every position
Optional without adjustable tilting [S506]
- **Electrical safety valves** on all cylinders
- All pins are galvanised and chromed
- **Low maintenance bushes fitted to all pivot points**
- **Cylinder piston rods in chromed stainless steel (INOX)**
- Compact power pack with **noise-dampening** cover
- External control in closed synthetic box
- **Control unit without electronic components**
- Equipment in conformity with CE safety regulations

TECHNICAL SPECIFICATIONS:

- Approx. centre of gravity **proper weight** : 800 mm
- Centre of gravity **of the load** : 750 mm
- Max. depth rear of floor : 250 mm
- Lift arm center : 2310 mm
- Standard platform depths : 1300 - 1500 - 1700 mm
The standard execution of the 1300 mm platform foresees 2 hinged leading edges and 2 side loading ramps
- Standard platform width : 2450 mm
- **INDICATION ON THE PROPER WEIGHT FOR DH-SK :**

Lift capacity	Platform depth		
	1300 mm	1500 mm	1700 mm
1500 kg	680 kg	710 kg	740 kg
2000 kg	710 kg	740 kg	770 kg
2500 kg	730 kg	760 kg	790 kg

The proper weights mentioned are indicative, and may vary according to the specific data of the vehicle and tail lift. Dhollandia reserves the right to modify the technical specifications without prior notice.

MAIN OPTIONS:

- [S001] Wander lead with spiral cable (*)
- [S003] Fixed internal control with 2 buttons (*)
- [S402] **Bolt-on fitting with clamping plates**
- [S506] Execution without adjustable tilting
- [S701] **Two piece hinged leading edge to form a stop**

(*) The use of certain additional controls is restricted under the CE safety regulations. Consult our users manual for further information.

Your dealer:

